

Network Disk Recorder

H.265/H.264 high-throughput featuring integrated GUI and robust embedded IP security enabling a secure end-to-end PC-less surveillance solution for mission-critical applications.

Supports full data encryption streaming recording for all i-PRO Extreme cameras which comply to FIPS 140-2 Level 1 standards to keep your video secured from spoofing and snooping activities.

Secure communication and high compression recording

- Significant reduction of storage space usage through H.265 and Smart Coding.
- 9 ch. expandable to 32 ch. camera input. Supports H.265 / H.264 mixed recordings.
- Symantec device certificates pre-installed *Secure Communication Kits are necessary.

PC-less non-VMS surveillance solution

- No camera license fees with a default number of cameras; no annual license updates required.
- Built-in GUI and Dual HDMI (4K/FHD) outputs
- Automatic camera configuration
- Image search with thumbnails
- High-speed copy to USB storage

High reliability and high efficiency data reading/writing

- Eco-writing: Acceleration of data access (reading/writing) by original file system
- Instantaneous power failure measures: Normal operation at instantaneous power failure within 200 ms; safe shutdown at power failure of 200 ms or more.

Applications

- Banks
- Retail / Quick-Service Restaurants
- Hospitals / Education
- Factories
- Gas Stations




Specifications

Supported Camera	Compatible vendor	Panasonic i-PRO series Network cameras, ONVIF NVT conformant camera and encoder	
	Supported Image Format	H.265(HEVC), H.264, JPEG	
	Supported Image Resolution (Depending on the camera)	•Aspect ratio [4 : 3] 4000x3000, 2560x1920, 2048x1536, 1280x960, 800x600, 640x480 •Aspect ratio [16 : 9] 3840x2160, 2560x1440, 1920x1080, 1280x720, 640x360 •Aspect ratio [1 : 1] 2992x2992, 2816x2816, 2048x2048, 1280x1280 •Aspect ratio [9 : 16] 1080x1920, 720x1280, 360x640	
	Supported Audio Format	G.711 for Onvif, G.726 (ADPCM) 32 kbps	
Recording	Maximum Number of Cameras	MAX. 32 ¹⁾ (Default number of cameras : 9)	
	Recording Mode	Event, Schedule, Emergency	
	Pre-alarm Recording	Up to 15 seconds *When the delivery speed from the network camera is less than 4 Mbps.	
	Scheduled Recording Mode	16 programs, 6 time zones/day, Independent setup for each day of the week	
Main Unit Functions	Camera Control	Pan/Tilt, Zoom, Focus, Brightness, Preset position call and program (up to 256), Auto mode, Click centering, Wheel zoom, Zoom reset, Auto Back Focus, Aux, Wiper (for WV-SUD638)	
	Multiscreen Mode	[Main monitor] • Control screen 4 / 9 / 16 split screen display • Wide view screen 3 / 4 / 6 / 9 / 12 / 16 / 24 / 32 split screen display, 1 screen sequence, 4 / 9 / 16 split screen sequence [Sub monitor] 1 / 4 / 9 / 16 / 24 / 32 split screen display, 1 screen sequence, 4 / 9 / 16 split screen sequence	
	Playback Control	PLAY, Rev PLAY, Pause, Stop, FF, FR, Prev Record, Next Record, Prev Image, Next Image, Go to Date, Go to Last (30 s)	
	Search Mode	Search criteria : Time date, Playback by designating a timeline, VMD, Thumbnail Copy	
	Camera Title	Up to 16 Characters	
	Clock Display	Time : 12H/24H, Date : 5 formats	
	Digital Zoom	Live / Play: 1.25x 1.5x 1.75x 2x 2.5x 3x 3.5x 4x 5x 6x 7x 8x (only for 1-screen or 4-screen)	
	System Log	Operator access (500), Network error (100), Error (1,000), Event (1000), Operation (500)	
	System Setup	Setup page in English, French, Italian, Spanish, German, Russian, Portuguese, Thai, Simplified Chinese, Japanese	
	360 Camera Dewarp re-encoding	Only 1ch display mode. 2Client	
	SD Memory Data Download	Images recorded in the SD card in the i-PRO series cameras can be transferred to the recorder automatically. (H.265/H.264)	
	Browser GUI	Camera Control	Pan/Tilt, Zoom, Focus, Brightness, Preset position call and program (up to 256), Auto mode, Click centering, Wheel zoom, Zoom reset, , Aux, Wiper (for WV-SUD638)
		Playback Control	PLAY, Rev PLAY, Pause, Stop, FF, FR, Prev Record, Next Record, Prev Image, Next Image, Go to Date, Go to Last (30 s)
		Search Mode	Search criteria: Time date, Event type, VMD, Camera number
		Display Mode	1 / 4 screen
		Image Download	Recorded data of selected camera and time range can be downloaded to a PC. Viewer software can be downloaded separately.
Copy		Recorded data of selected cameras and time date range can be copied to the USB storage.	
Camera Title		Up to 16 characters	
Clock Display		On the browser. Time: 12H/24H, Date: 5 formats	
Alarm Control		Reset	
Digital Zoom		Live/Play: 2x, 4x (only for 1-screen)	
System Log		Operator access (500), Network error (100), Error (1,000), Event (1000), Operation (500)	
GUI Language		Setup page in English, French, Italian, Spanish, German, Russian, Portuguese, Thai, Simplified Chinese, Japanese	
Required PC		CPU: Intel® Core™ i7-8600 or faster, RAM : 4 GB or more, VRAM: 128 MB or more (Min. 64 MB), Microsoft® DirectX® 9.0c or later	

*1 Three Additional Camera Kits WJ-NXE20 are necessary. *2 Non-voltage make contact input, +3.3 V pull-up Approx. 23 kΩ. *3 Open collector output, 24 V DC, -200 mA max. *4 +5V ±0.5 V 200 mA max. *5 Additional Business Intelligence Kit WJ-NXF02 is necessary. *6 Feature update *7 Panasonic Security Viewer v.3.0 or later is required on smartphone/tablet PC. *8 Please check the following URL for the latest information. (<http://security.panasonic.com/download/library/>)

Alarm/Event	Alarm Source	9x Terminal inputs, 32x Camera alarms (Panasonic Alarm Protocol), 128x Command alarms	
	Event Mode	Off / On	
	Alarm Action	Alarm recording, e-mail notification, Alarm message, Camera positioning, Terminal output, Panasonic alarm protocol output, Buzzer, Indicator	
	Alarm Control	Reset	
Input / Output	Event log	1000	
	Spot Output Connector	1x 1 V [p-p] / 75 Ω (BNC) NTSC / PAL (selectable in setup menu)	
	Monitor (HDMI) Connector	[Main monitor] HDMI 4K UHD(3840x2160p) /30Hz, 4K UHD(3840x2160p) /25Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1920x1080i /60Hz, 1920x1080i /50Hz [Sub monitor] HDMI 1920x1080p /60Hz, 1920x1080p /50Hz, 1920x1080i /60Hz, 1920x1080i /50Hz	
	Audio Output Connector	-10 dBv, 600 Ω, unbalanced x1 (RCA pin jack)	
	Alarm / Control Terminal	Alarm input 1 - 9 ²⁾ , Alarm output ³⁾ , Alarm reset input ²⁾ Control Time adjustment input/output ²⁾ , +5 V output ⁴⁾ Error/Warning Network error output ³⁾ , HDD error output ³⁾ , Camera error output ³⁾ , Recorder error output ³⁾ , Recording error output ³⁾ , Face matching output ⁵⁾ , Emergency recording input	
	Mouse Connection Port	2 (Front 1, Rear 1)	
	Network Port	2x 10BASE-T / 100BASE-TX / 1000BASE-T (RJ45)	
	USB Storage	USB 3.0 / USB 2.0 memory, USB 3.0 / USB 2.0 connected HDD (except bus powered device)	
	Network	Network Interface	2x 10BASE-T / 100BASE-TX / 1000BASE-T (RJ45)
		Maximum Recording Rate	192 Mbps or less
Maximum Band Width		Total 384 Mbps or less	
Supported Protocol		IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, FTP, SMTP, DNS, NTP, SNMP, RTP, RTSP, ICMP, ARP IPv6: ICMPv6	
E-mail		Upon Alarm or Warning	
No. of Simultaneous Users		16 or less	
User Registration		Up to 32 users	
User Level		3 Levels (Programmable)	
Partitioning		User level - Camera (View & Control, No Access)	
Security Method		User authentication (ID and Password), Host authentication, Alteration detection, SSL/TLS	
Other Functions	Time Synchronization	Terminal (Master/Slave), NTP (Server/Client)	
	Summer Time	User definable (using menu setup)	
	Remote Monitoring on Smartphone/Tablet	16 clients or less ⁷⁾	
HDD	Type	8.89 cm (3.5 inch) Serial ATA HDD, Up to 2x HDDs can be installed.	
	Maximum Capacity	Up to 12 TB will be supported. ⁸⁾	
	RAID	RAID 1	
Viewer Software	Playback Control	Play, Rev Play, Pause, FF, FR, Prev Record, Next Record, Prev Image, Next Image	
	Additional Functions	Alteration detection, Save as JPEG, Two times zoom, Print, Copy, Aspect ratio switching, fish eye correction, corridor display ⁶⁾	
	Supported OS, Language	Language of the software will be English or Japanese	
General Specifications	Safety / EMC Standard	CE (EN60065, EN55032 ClassB, EN55024), EAC	
	Power Source	220 V-240 V AC 50 Hz/60 Hz	
	Power Consumption	approx. 56 W	
	Ambient Operating Temperature	Main body : +5 °C to +45 °C (41 °F to 113 °F) Mouse (provided) : +5 °C to +40 °C (41 °F to 104 °F)	
	Ambient Operating Humidity	5 % to 90 % (without condensation)	
	Maximum Operating Altitude	2,000 m (6,562 feet) above sea level	
	Dimensions	420 mm(W) x 88 mm(H) x 300 mm(D) {16-9/16 inches (W) x 3-7/16 inches (H) x 11-13/16 inches (D)}	
Mass (approx.)	When no HDD is installed: 5.2 kg (11.5 lbs)		

Appearance



Trademarks and registered trademarks

- "i-PRO" logo is trademarks or registered trademarks of Panasonic Corporation.
- HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.
- ONVIF and the ONVIF logo are trademarks or registered trademarks of ONVIF Inc.
- All other trademarks identified herein are the property of their respective owners.

Important

- Safety Precaution : Carefully read the Important Information, Installation Guide and operating instructions before using this product.
- Panasonic cannot be responsible for the performance of the network and/or other manufacturers' products used on the network.

• Masses and dimensions are approximate. • Specifications are subject to change without notice.

Optional Accessories

Additional Business Intelligence Kit WJ-NXF02, WJ-NXF02W

Feature Update

WJ-NXF02(W) is a license kit intended to improve the usefulness of Network Disk Recorder WJ-NX200. After registering the WJ-NXF02(W) into WJ-NX200, WJ-NX200 is enabled statistical processing functions such as "People counting" and "Face matching / Age & Gender judgment". *2ch input per license



Additional Camera Kits

Number of cameras used in the system can be increased to 32 (maximum) by purchasing the Additional Camera Kits (WJ-NXE20, WJ-NXE20W : three license for 32 cameras).

Secure Communication Kits

The Secure Communication Kits are license kits to use the security function of the network disk recorder. Each Secure Communication Kit allows the following number of cameras to be registered.

WJ-NXS01, WJ-NXS01W	WJ-NXS04, WJ-NXS04W	WJ-NXS16, WJ-NXS16W	WJ-NXS32, WJ-NXS32W
1 camera	4 cameras	16 cameras	32 cameras

Rack Mount Bracket WV-Q202



DISTRIBUTED BY :

Panasonic

<http://security.panasonic.com>



<http://www.facebook.com/PanasonicNetworkCamera>